

Weidezaungeräte Übersicht

																			
Gerät																			
 230 Volt Netzgeräte		N 700	10.000 V	0,55 J	5,0 km	1,0 km	0,5 km	•		•						•	•	•	
		N 1200	12.500 V	1,20 J	10,0 km	2,0 km	1,0 km	•		•		•		•	•	•	•	•	
		N 3500	11.500 V	3,50 J	20,0 km	6,0 km	2,5 km	•	•	•	•	•	•						
		N 4800	9.000 V	4,80 J	30,0 km	8,0 km	4,0 km	•	•	•	•	•	•						
		N 5000	10.000 V	5,00 J	45,0 km	8,0 km	4,5 km	•	•	•	•	•	•						
		Ni 7000	9.700 V	7,00 J	70,0 km	15,0 km	7,5 km	•	•	•	•	•	•						
		Ni 10000	10.200 V	10,00 J	80,0 km	18,0 km	9,0 km	•	•	•	•	•	•						
		NDi 6500	9.700 V	6,50 J	60,0 km	12,0 km	6,0 km	•	•	•	•	•	•						
		NDi 10000	10.200 V	10,00 J	80,0 km	18,0 km	9,0 km	•	•	•	•	•	•						
		NDi 15000	10.200 V	14,50 J	100,0 km	22,0 km	12,0 km	•	•	•	•	•	•						
 DUO Geräte (12 V / 230 V)		X 1000	12.000 V	1,00 J	10,0 km	1,5 km	0,8 km	•		•				•	•	•	•	•	
	X 1500	12.000 V	1,50 J	14,0 km	2,7 km	1,5 km	•	•					•	•					
	X 2500	9.600 V	2,00 J	18,0 km	4,0 km	1,7 km	•		•	•	•								
	X 4000	9.600 V	3,00 J	35,0 km	12,0 km	5,0 km	•	•	•	•	•	•							
 12 Volt Akkugeräte		Savanne 2000	9.600 V	1,90 J	20,0 km	5,0 km	2,0 km	•		•	•	•		•			•	•	
		Savanne 3000	9.600 V	3,00 J	35,0 km	12,0 km	5,0 km	•		•	•	•		•				•	
		A 2000	9.600 V	2,00 J	18,0 km	4,0 km	1,7 km	•		•	•	•		•	•	•		•	
		A 3300	10.200 V	3,30 J	28,0 km	6,0 km	3,0 km	•		•	•	•		•	•	•		•	
		A 1200	10.700 V	1,40 J	10,0 km	5,0 km	1,5 km	•		•		•		•	•	•	•	•	
		AD 2000 digital	10.500 V	2,10 J	20,0 km	8,0 km	3,0 km	•	•	•	•	•			•			•	
		AD 3000 digital	10.800 V	3,00 J	30,0 km	10,0 km	4,0 km	•	•	•	•	•	•	•					
		AD 5000 digital	11.000 V	4,60 J	38,0 km	14,0 km	5,5 km	•	•	•	•	•	•						
		AN 3100	10.200 V	3,50 J	33,0 km	12,0 km	4,5 km	•	•	•	•	•	•						
		AN 5500	10.300 V	4,80 J	43,0 km	17,0 km	7,0 km	•	•	•	•	•	•						
AN 5500 digital		10.000 V	5,00 J	23,0 km	9,0 km	3,5 km	•	•	•	•	•	•							
 Solar (12 V)		S 550	8.100 V	0,55 J	6,0 km	2,0 km	1,0 km	•		•						•	•	•	
		S 180	8.000 V	0,18 J	2,0 km	0,5 km	-	•		•						•	•	•	
 9 Volt Trockenbatteriegeräte		B 40	7.500 V	0,04 J	0,2 km	-	-	•		•							•	•	•
		B 140	8.400 V	0,16 J	2,0 km	0,5 km	-	•		•					•		•	•	
		B 240 multi	8.800 V	0,24 J	3,0 km	0,6 km	-	•		•		•		•	•	•	•	•	•
		B 250 plus	10.500 V	0,25 J	3,0 km	0,7 km	-	•		•					•	•	•	•	•
		B 290	10.500 V	0,29 J	5,0 km	2,0 km	-	•		•		•		•	•	•	•	•	•
		B 500 plus	9.000 V	0,50 J	9,0 km	6,0 km	1,8 km	•		•		•		•	•	•	•	•	•
		BD 300 digital	11.000 V	0,30 J	6,0 km	4,0 km	1,5 km	•		•					•	•	•	•	•
	BD 400 digital	11.400 V	0,40 J	8,0 km	5,5 km	1,7 km	•		•					•	•	•	•	•	
	BD 600 digital	11.700 V	0,55 J	10,0 km	7,0 km	2,0 km	•		•		•			•	•	•	•	•	